

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-519-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-520-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-521-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-522-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1316 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-523-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-524-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-525-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-526-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-527-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-528-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-529-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-530-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-531-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-532-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-533-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-534-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-535-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-536-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-537-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-538-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-539-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-540-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-541-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-542-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-543-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-544-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-545-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-546-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-547-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-548-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-549-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-550-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-551-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-552-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-553-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-554-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-555-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-556-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-557-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-558-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-559-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-560-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-561-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-562-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-563-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-564-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-565-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-566-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-567-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-568-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-569-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1511 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-570-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1512 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-571-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1513 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-572-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1514 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-573-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1515 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-574-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1516 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-575-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-576-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-577-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-578-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-579-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1521 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-580-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1522 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-581-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1523 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-582-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1524 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-583-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1525 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-584-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1526 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-585-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-586-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-587-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-588-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-589-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1531 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-590-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1532 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-591-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1601 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-592-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1602 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-593-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1603 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-594-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1604 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-595-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1605 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-596-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1606 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-597-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1607 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-598-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1608 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-599-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1609 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-600-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1610 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-601-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1611 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-602-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1612 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-603-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1625 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-2321-604-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:

62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1626 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.